

APPENDIX D

**Dam Cross Section Profiles and Preliminary
Design Layouts for Dam Structures and
Appurtenant Features**




Fine Gold Reservoir

Appendix D contains preliminary, pre-feasibility level design drawings of the dam structures and appurtenant features that are being considered as surface storage options for Fine Gold Reservoir. They were prepared in order to develop estimates of quantities of materials that would be needed to construct the features, for inclusion in construction cost estimates, and to facilitate future planning. Designs for retained options will be refined as the Investigation progresses.

Sample cross section profiles for each dam type (CFRF, RCC) are presented first, followed by plan view layouts for the surface storage options.

The figures are displayed in the following order:

- RCC cross section profile
- CFRF cross section profile
- RCC crest elevation 900
- CFRF crest elevation 900
- RCC crest elevation 1,100
- CFRF crest elevation 1,100




NOTES

1. Foundation for RCC gravity dam to be excavated to competent rock.

FILE PATH: H:\CASSO Share\Drawing Files\Upper San Joaquin\ PLOTTED BY: RLUNBAR SEPTEMBER 30, 2002 10:58

ALWAYS THINK SAFETY	
UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION UPPER SAN JOAQUIN PROJECT CALIFORNIA	
UPPER SAN JOAQUIN STORAGE INVESTIGATIONS ROLLER COMPACTED CONCRETE DAM	
FIGURE 1	
CADD SYSTEM AUTOCAD Rev. 15.06 DENVER, COLORADO	CADD FILENAME FTGURE1.DWG AUGUST 13, 2002 SHEET 1 OF 2
ZU-D-FIG 1	
SOLICITATION NO. 0000	




PLAN

EMBANKMENT EXPLANATION


- ①A Clay, silt, sand, and gravel with a maximum particle size of 3-inches (> 12% fines) from borrow compacted to 6-inch layers
- ①B Gravel and cobbles with a maximum particle size of 12-inches from required excavation and borrow compacted to 18-inch layers.
- ② Silty gravel with sand processed from borrow compacted to 18-inch layers.
- ③A Gravel processed from borrow compacted to 18-inch layers.
- ③B Rock fill with a maximum particle size of 18-inch compacted to 36 inch layers.
- ③C Rock fill with a maximum particle size of 36-inches compacted to 48-inch layers.

NOTES

1. Cofferdam foundation conditions assumed to be coarse gravel, cobbles and boulders.
2. Foundation for shells assumed to be competent rock cleaned by standard construction equipment.
3. Foundation for toe slab assumed to be competent rock cleaned by hand and surface treated.





DETAIL A



DETAIL B


ALWAYS THINK SAFETY	
UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF RECLAMATION UPPER SAN JOAQUIN PROJECT CALIFORNIA	
UPPER SAN JOAQUIN STORAGE INVESTIGATIONS CONCRETE FACED ROCKFILL DAM	
FIGURE 2	
CADD SYSTEM AutoCAD Rev. 15.06 DENVER, COLORADO	CADD FILENAME FT09R22.DWG AUGUST 13, 2002 SHEET 2 OF 2

DATE AND TIME PLOTTED
 SEPTEMBER 30, 2002 11:02
 PLOTTED BY
 JWH/TFE



NOTES

Saddle dam on right reservoir rim not shown.



ALWAYS THINK SAFETY


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF RECLAMATION
UPPER SAN JOAQUIN RIVER BASIN
STORAGE INVESTIGATION
CALIFORNIA

**LAYOUT FOR DAM STRUCTURE
AND APPURTENANT FEATURES**

FINE GOLD RCC DAM
CREST EL. 900


CADD SYSTEM Autocad	CADD FILENAME FINE GOLD DAM
DENVER, COLORADO	SEPTEMBER 25, 2002

DATE AND TIME PLOTTED
10-01-02
PLOTTED BY
JPROVER



NOTES

Downstream Cofferdam not shown. Downstream Cofferdam with crest elevation 578 will be incorporated into downstream dam embankment.



ALWAYS THINK SAFETY

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF RECLAMATION
UPPER SAN JOAQUIN RIVER BASIN
STORAGE INVESTIGATION
CALIFORNIA


**LAYOUT FOR DAM STRUCTURE
AND APPURTENANT FEATURES**

FINE GOLD CFR DAM
CREST EL. 900


CADD SYSTEM
AutoCAD
DENVER, COLORADO

CADD FILENAME
SEPTEMBER 25, 2002

DATE AND TIME PLOTTED
10-01-02
PLOTTED BY
JPROVER



NOTE
Saddle dam on right reservoir rim not shown.



ALWAYS THINK SAFETY


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF RECLAMATION
UPPER SAN JOAQUIN RIVER BASIN
STORAGE INVESTIGATION
CALIFORNIA

LAYOUT FOR DAM STRUCTURE
AND APPURTENANT FEATURES

FINE GOLD RCC DAM
CREST EL. 1100


CADD SYSTEM Autocad	CADD FILENAME
DENVER, COLORADO	SEPTEMBER 25, 2002

DATE AND TIME PLOTTED
10-01-02
PLOTTED BY
JROVER



NOTES

Saddle dam on right reservoir rim not shown.
 Downstream cofferdam not shown. Downstream Cofferdam with crest elevation 578 will be incorporated into downstream dam embankment.



 **ALWAYS THINK SAFETY**

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 BUREAU OF RECLAMATION
 UPPER SAN JOAQUIN RIVER BASIN
 STORAGE INVESTIGATION
 CALIFORNIA

**LAYOUT FOR DAM STRUCTURE
 AND APPURTENANT FEATURES**

FINE GOLD CFR DAM
 CREST EL. 1100

CADD SYSTEM AutoCAD	CADD FILENAME
DENVER, COLORADO	SEPTEMBER 25, 2002

DATE AND TIME PLOTTED
 10-01-02
 PLOTTED BY
 JPROVER

APPENDIX E

Climate Data

Fine Gold Reservoir

FRIANT GOVERNMENT CAMP, CALIFORNIA (043261)

Period of Record Monthly Climate Summary

Period of Record : 7/ 1/1948 to 3/31/2003

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Annual
Average Max. Temperature (F)	55.2	61.2	66.0	73.9	84.0	92.9	100.0	98.5	92.3	81.6	66.6	55.9	77.3
Average Min. Temperature (F)	36.4	39.5	40.9	43.3	48.9	55.2	60.5	59.2	55.8	49.1	41.4	36.2	47.2
Average Total Precipitation (in.)	2.70	2.45	2.42	1.29	0.47	0.16	0.01	0.01	0.24	0.67	1.64	2.15	14.22
Average Total SnowFall (in.)	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Average Snow Depth (in.)	0	0	0	0	0	0	0	0	0	0	0	0	0

Percent of possible observations for period of record.

Max. Temp.: 99.4% Min. Temp.: 99.4% Precipitation: 99.4% Snowfall: 99.4% Snow Depth: 99.4%

Source: Western Regional Climate Center, Desert Research Institute
<http://www.wrcc.dri.edu/cgi-bin/cliMAIN.pl?cafria+nca>

THIS PAGE LEFT BLANK INTENTIONALLY